

Antique Metal

PRODUCT DESCRIPTION	IT is specially formulated paint for decorative purposes to give shine color for wooden surface and steel works which used as a frame.
----------------------------	--

RECOMMENDED USES	For wood , steel and gypsum board decoration
-------------------------	--

TECHNICAL DATA

COLOUR, DRY FILM	Gold, Bronze, Silver, Green, Lemon, copper.
FINISH, DRY FILM	Smooth
VOLUME SOLIDS (ASTM D2697)	38± 1%
SPECIFIC GRAVITY	1.10+2 g/m
THEORETICAL SPREADING RANGE	Spreading rate 4-5 lit in 2 coats.
RECOMMENDED DFT RANGE (DRY FILM THICKNESS)	30 – 40 Microns/Coat
RECOMMENDED WFT RANGE (WET FILM THICKNESS)	70 – 95 Microns/Coat
FLEXIBILITY	Good

DRYING TIME

	5° C	10° C	15° C	20° C	25° C
TOUCH DRY					1/2 hour
DRY TO RECOAT*					1 hours
FULL DRY					24 hours

Drying time (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.)

*For same generic type paint.

ADVANTAGES

ANTIQUÉ METAL	Shine color for wooden surface and steel works which used as a frame .
----------------------	--

APPLICATION INSTRUCTION

SURFACE PREPARATION	The surface should be dry, clean and crack free. Apply deco primer and deco top over wooden or steel surfaces
----------------------------	---

APPLICATION DATA

APPLICATION METHOD	By brush
CLEANING/THINNING	Ready to use / cleaning with Thiner.
THINNER (VOLUME)	5% depends on the method of application

SYSTEM

RECOMMENDED SYSTEM To be applied on prepared surface.	. Deco primer
	. Deco paint

HEALTH & SAFETY

SAFETY PRECAUTIONS	<ul style="list-style-type: none"> - Keep away from fire and out of reach of children. - Keep working area well ventilated - Do not mix this product with any other not recommended by us
---------------------------	--

STORAGE & PACK SIZE

STORAGE	Keep the sealed original container away from direct sun. Store in temperature 5 – 35°C..
PACK SIZE	¼ litre

Health , Safety & Environmental Information

<ul style="list-style-type: none"> - Read the label and product information before use the product. - Ensure good ventilation during application and drying. - Avoid contact with eyes ,rinse immediately with plenty of water and seek medical advice. - Don` t breath spray , when spraying in confined spaces, wearing cartridge mask . - Avoid contact with skin ,wash immediately with plenty of soap and water or a proprietary skin cleaner ,don` t use solvent thinner or white spirit. - Keep out of the reach of children. - If swallowed, seek medical advice immediately and show this container or label. - Don` t use or store by hanging on a hook .Don` t empty into drains or watercourses. - Avoid the inhalation of dust . Wear a suitable face mask if dry sanding.
--