



Drup Supercryl

PRODUCT DESCRIPTION	An acrylic paint , matt finish with superior adhesion and very good durability in all climatic conditions .
----------------------------	---

Exterior Interior

RECOMMENDED USES	For exterior and interior painting of plaster ,concrete ,bricks ,asbestos cement .
-------------------------	--

TECHNICAL DATA

COLOUR, DRY FILM	As per shade card
FINISH, DRY FILM	Matt
VOLUME SOLIDS (ASTM D2697)	60 % ± 2
SPECIFIC GRAVITY	1.5 g/ml
THEORETICAL SPREADING RANGE	4 m ² /lit.
RECOMMENDED DFT RANGE (DRY FILM THICKNESS)	42 – 57 Microns/Coat
RECOMMENDED WFT RANGE (WET FILM THICKNESS)	70 – 95 Microns/Coat
FLASH POINT	Water base
FLEXIBILITY	Good

DRYING TIME

	5° C	10° C	15° C	20° C	25° C
TOUCH DRY					2 hour
DRY TO RECOAT*					4 hours
FULL DRY					24 hours

Drying time (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.)

*For same generic type paint.



ADVANTAGES

Drup Supercryl	Excellent washable for exterior and interior walls.
-----------------------	---

APPLICATION INSTRUCTION

SURFACE PREPARATION	<p>Surface should be cleaned thoroughly, dry and free from dust and dirt.</p> <p>New asbestos : Clean and rinse thoroughly with a strong stream of water, allow to dry fully, apply one coat of bonder super, allow to dry and apply 2 coats of Drup Supercryl.</p> <p>Aged asbestos cement (after exterior exposure) Clean surface from dust, dirt, and grease. Apply first coat of Drup Supercryl . thinned with 20% water, allow 3 hours to dry, then apply 2 additional coats thinned with 10%-15% water.</p>
----------------------------	---

APPLICATION DATA

APPLICATION METHOD	Brush, Roller, airless spray .
CLEANING/THINNING	Water .
THINNER (VOLUME)	5 – 10% depends on the method of application
CONV. SPRAY REQUIREMENTS	Atomizing pressure: 50 psi
AIRLESS SPRAY REQUIREMENTS	Pressure : 2000 – 2200 psi
NOZZLE SIZE	0.018” – 0.020”
MIXING RATIO (BY VOLUME)	Not applicable
POT LIFE @ 30°c (100 ml)	Not applicable

RECOMMENDED SYSTEM

1- Internal use	Super Bendrol	: 1 coat
	Soft Bond	: 1 coat
	Drup Supercryl	: 2 Coats
2- External use	Super bendrol	: 1 Coat
	Drup Supercryl	: 2 Coats

HEALTH & SAFETY

SAFETY PRECAUTIONS	<ul style="list-style-type: none"> - Keep away from fire and out of reach of children. - Keep working area well ventilated - Do not mix this product with any other not recommended by us.
---------------------------	---

STORAGE & HANDLING

STORAGE	Keep the sealed original container away from direct sun. Store in temperature 5 – 35°C.
PICK SIZE	18lit.5lit.

Health , Safety & Environmental Information

- Read the label and product information before use the product.
- Ensure good ventilation during application and drying.
- Avoid contact with eyes ,rinse immediately with plenty of water and seek medical advice.
- Don`t breath spray , when spraying in confined spaces, wearing cartridge mask .
- Avoid contact with skin ,wash immediately with plenty of soap and water or a proprietary skin cleaner ,don`t use solvent thinner or white spirit.
- Keep out of the reach of children.
- If swallowed, seek medical advice immediately and show this container or label.
- Don`t use or store by hanging on a hook .Don`t empty into drains or watercourses.
- Avoid the inhalation of dust . Wear a suitable face mask if dry sanding.

