



APC ANTIQUE TERRE
DECORATIVE – INTERNAL PAINTS

TECHNICAL DATA SHEET

Antique Terre

PRODUCT DESCRIPTION	Water based wall covering containing an aqueous dispersion of acrylic polymers organic and inorganic pigments various additives (thickening agents, antifoaming and others).
----------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

RECOMMENDED USES	For concrete, gypsum boards plaster and wood work.
-------------------------	----------------------------------------------------

TECHNICAL DATA

COLOUR, DRY FILM	White or as per shade card.
FINISH, DRY FILM	Lightly rough mat or semi gloss.
VOLUME SOLIDS (ASTM D2697)	55 %
SPECIFIC GRAVITY	1.05 ±1 g/ml . .
THEORETICAL SPREADING RANGE	6-8 m ² /ltr .
RECOMMENDED DFT RANGE (DRY FILM THICKNESS)	30 – 40 Microns/Coat
RECOMMENDED WFT RANGE (WET FILM THICKNESS)	70 – 95 Microns/Coat
FLEXIBILITY	Good

DRYING TIME

	5° C	10° C	15° C	20° C	25° C
TOUCH DRY					1 hours
DRY TO RECOAT*					4 hours
FULL DRY					24 hours

Drying time (Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.)

*For same generic type paint.



ADVANTAGES

APC ANTIQUE TERRE	Excellent for concrete, gypsum boards plaster and wood work.
--------------------------	--------------------------------------------------------------

APPLICATION INSTRUCTION

SURFACE PREPARATION	If the surface needs to be prepared before painting ,Bendrol super and soft bond PVA are ideal. The two coat of emulsion 101 or Aracryl 101 is required as a primer before application of Terre by brush and trowel.
----------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

APPLICATION DATA

APPLICATION METHOD	Brush and trowel.
CLEANING/THINNING	Water .
THINNER (VOLUME)	5 – 10% depends on the method of application

SYSTEM

RECOMMENDED SYSTEM To be applied on prepared surface.	Bendrol super	:1coat
	Soft bond	: 1coat
	Emulsion 101 or Aracryl 101	:2coats
	ANTIQUE TERRE.	: 1coat

HEALTH & SAFETY

SAFETY PRECAUTIONS	<ul style="list-style-type: none">- Ensure good ventilation during application and drying. - Avoid contact with skin & eyes. When painting it is advisable to wear eye protection in case of contact with eyes, rinse immediately with plenty of water & seek medical advice. Remove splashes from skin. - Keep out of reach of children
---------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

STORAGE &PACK SIZE

STORAGE	The product must be stored in according with international regulations. the, product should be kept in cool and well ventilated, protected from heat and direct sunlight. containers must be kept tightly closed .
PICK SIZE	1lit . 5 lit .

Health , Safety & Environmental Information

- Read the label and product information before use the product.
- Ensure good ventilation during application and drying.
- Avoid contact with eyes ,rinse immediately with plenty of water and seek medical advice.
- Don` t breath spray , when spraying in confined spaces, wearing cartridge mask .
- Avoid contact with skin ,wash immediately with plenty of soap and water or a proprietary skin cleaner ,don` t use solvent thinner or white spirit.
- Keep out of the reach of children.
- If swallowed, seek medical advice immediately and show this container or label.
- Don` t use or store by hanging on a hook .Don` t empty into drains or watercourses.
- Avoid the inhalation of dust . Wear a suitable face mask if dry sanding.

